

AMICO Metal Lath – Data Submittal Sheet

Project: _____
Location: _____ Contractor: _____
Distributor: _____ Date: _____


Please indicate which of the following will be used in this project:

Metal Lath




- Weight: 1.75 lb/sq. yard
 2.5 lb/sq. yard
 3.4 lb/sq. yard
- Type: Dimpled Flat V-Groove

Spray Lath (using Kraft paper)




- Weight:
 3.4 lb/sq. yard - V-Rib Lath
(Optional sheet size 27" x 48")
 2.75 lb/sq. yard - 1/8" Flat Rib Lath
 3.4 lb/sq. yard - 1/8" Flat Rib Lath
 3.4 lb/sq. yard - 3/8" High Rib Lath

1/8" Rib Lath (Flat Rib)




- Weight: 2.75 lb/sq. yard
 3.4 lb/sq. yard

Tilath




- Lath Type: Flat Dimpled
 V-Groove
- Paper: Grade D (Fed Spec UU-B-790a)
 60 minute Grade D
- Weight: 1.75 lb/sq. yard
 2.5 lb/sq. yard
 3.4 lb/sq. yard
 2.75 lb/sq. yard 1/8" Flat Rib

3/8" Rib Lath (High Rib)



- Weight: 3.4 lb/sq. yard
 4.0 lb/sq. yard

Stainless Steel Lath (Flat)



- Type: Alloy 304 Alloy 316
- Weight: 1.75 lb/sq. yard
 2.5 lb/sq. yard
 3.4 lb/sq. yard
- Produced as flat lath only

All AMICO lath is produced from G-60 pre-galvanized steel, conforming to ASTM C-847 and A-653. Lath sheets to be installed according to ASTM C-1063. See AMICO catalog for installation instructions.

Sheet size: approximately 27" x 96" (covers 2 sq. yards or 18 sq. feet)

Sheet weight: 3.5 lb. (1.75 lb./sq. yard); 5.0 lb. (2.5 lb./sq. yard); 6.8 lb. (3.4 lb./sq. yard), +/- 10%

Packaging: 10 sheets/bundle; 25 bundles/pallet (Tilath, Dimpled and Spray Lath types);
50 bundles/pallet (Flat, V-groove, Rib Lath)

QUALITY PRODUCTS – COAST TO COAST



A GIBRALTAR INDUSTRIES COMPANY 

ALABAMA METAL INDUSTRIES CORPORATION

3245 Fayette Ave. • Birmingham, AL 35208 • Phone (205) 787-2611 • (800) 366-2642 • Fax (205) 786-6527

www.amico-lath.com