



Corporate Headquarters:
17635 NE 67th Ct.
Redmond, WA 98052
(800) 548-1231
www.permachink.com

Manufacturing:
1605 Prosser Road
Knoxville, TN 37914
(800) 548-3554

LIFELINE Exterior™

Product Description: Our original exterior wall formula has been updated and improved for over twenty years. Lifeline Exterior™ forms a thin film at the surface of logs where the protection is needed. Its breathability and flexibility allows logs to go through seasonal expansion and contraction while drying out to their core. Lifeline Exterior™ transparent stain provides excellent UV protection, high coverage rates and long lasting color retention.

Technical Data: Exterior Stain

- **Colors:** Available in ten colors.
- **Packaging:** 1 gal. container, 5 gal. pail, samples available.
- **Surface Preparation:** Must be applied to clean, dry surface.
- **Application Temperature Range, °F :** 40-90 ; Do not apply in direct hot sunlight.
- **Application Methods:** Airless Sprayer, brush.
- **Application Rates:** 1st Coat 350 -450 ft²/gal ; 2nd Coat 600 - 800 ft²/gal.
- **No. Coats:** 2 Coats + 1 Coat Advance Gloss/Satin.
- **Toxicity:** Non Toxic.
- **Shelf Life:** 1 Year.
- **Drying Times:** Dry to touch in 2-4 hours, Cures in 72 hours, however times will vary with temperature and humidity.
- **Clean-Up:** Soap and Water.
- **% Solids :** 17.5 - 20
- **VOC, g/L :** 232 [Regulatory Less Water]
- **Storage:** Freeze Thaw Stable
- **Viscosity, #2 Zahn C, 25°C :** 17.5 - 21.0
- **Density, lb./gal.:** 8.45- 8.70
- **Specific Gravity, SG:** 1.01-1.04
- **pH :** 8.80 - 9.30