



Corporate Headquarters:
17635 NE 67th Ct.
Redmond, WA 98052
(800) 548-1231
www.permachink.com

Manufacturing:
1605 Prosser Road
Knoxville, TN 37914
(800) 548-3554

LIFELINE Interior™

Product Description: Accent the beauty of all your interior wood and seal out household odors and contaminants. Lifeline Interior™ can be used as a color coat or sealing coat on walls when you want to apply an interior clear-coat for additional protection or luster. Interior finishes make log walls easy to clean. Lifeline Interior™ is breathable, has a high coverage rate, easy application and long lasting color retention.

Technical Data: Interior Stain

- **Colors:** Available in eleven colors plus a clear.
- **Packaging:** 1 gal. container, 5 gal. pail, samples available.
- **Surface Preparation:** Must be applied to clean, dry surface.
- **Application Temperature Range, °F :** 40-90
- **Application Methods:** Airless Sprayer, brush
- **Application Rates:** 1st Coat 350 -450 ft²/gal ; 2nd Coat 600 - 800 ft²/gal
- **No. Coats:** One or more depending on color desired. Topcoat with Acrylic Clear™ or Sure Shine™.
- **Toxicity:** Non Toxic.
- **Shelf Life:** 1 Year.
- **Drying Times:** Dry to touch in 1-4 hours, Cures in 72 hours, however times will vary with temperature and humidity.
- **Clean-Up:** Soap and Water.
- **% Solids :** 17 - 19
- **VOC, g/L :** 206 [Regulatory Less Water]
- **Storage:** Freeze Thaw Stable
- **Viscosity, #2 Zahn C, 25°C :** 18.0 - 24.0
- **Density, lb./gal.:** 8.40 - 8.60
- **Specific Gravity, SG:** 1.01 - 1.03
- **pH :** 8.00 - 8.60