



Corporate Headquarters:
17635 NE 67th Ct.
Redmond, WA 98052
(800) 548-1231
www.permachink.com

Manufacturing:
1605 Prosser Road
Knoxville, TN 37914
(800) 548-3554

LIFELINE Ultra 2™

Product Description: No other transparent finish system last as long as Lifeline Ultra 2™ with a clear topcoat of Lifeline Advance™. It is so durable that it is covered by a 5-year limited warranty. This advanced waterborne formula enriches the look of natural wood grain and protects your home against damaging UV rays from the sun. This system also features a breathable film allowing unseasoned logs to dry out. Finally, Lifeline Ultra 2™, has been shown through exposure studies to have superior color retention compared to our competitors.

Technical Data: Exterior Stain

- **Colors:** Available in sixteen colors.
- **Packaging:** 1 gal. container, 5 gal. pail, samples available.
- **Surface Preparation:** Must be applied to clean, dry surface.
- **Application Temperature Range, °F :** 40-90 ; Do not apply in direct hot sunlight.
- **Application Methods:** Airless Sprayer, brush.
- **Application Rates:** 1st Coat 350 -450 ft²/gal ; 2nd Coat 600 - 800 ft²/gal.
- **No. Coats:** 2 Coats + 1 Coat Advance Gloss/Satin.
- **Toxicity:** Non Toxic.
- **Shelf Life:** 1 Year.
- **Drying Times:** Dry to touch in 2-4 hours, Cures in 72 hours, however times will vary with temperature and humidity.
- **Clean-Up:** Soap and Water.
- **% Solids :** 18 - 20
- **VOC, g/L :** 224 (Regulatory Less Water)
- **Storage:** Freeze /Thaw Stable
- **Viscosity, #2 Zahn C, 25°C :** 17.5 - 21.0
- **Density, lb./gal.:** 8.45- 8.65
- **Specific Gravity, SG:** 1.01-1.04
- **pH :** 8.80 - 9.30